

Materials Handling Centrifugal



SPECIAL
CONFIGURATIONS
AVAILABLE

Backward Inclined, Radial Tip and Radial Bladed fans.

Rugged steel impeller is ideal for dust conveying or other industrial airstreams, erosive installations and material handling applications

- Materials handling
- Heavy Industrial Duty
- Direct or belt drive
- IP55 motor
- Sizes from 125mm to 420mm in diameter
- Motor Power- 0.75kW to 11kW
- Air Volume- 360L/s to 3,280L/s
- Static Pressure - 400Pa to 1,500Pa



MODEL No.	INLET DIAMETER (mm)	OUTLET (mm)	FAN (RPM)	MOTOR SPEED (RPM)	MOTOR POWER (kW)	AIR VOLUME (L/S)	STATIC PRESSURE (PA)
6-46-10A	125	120x140	Arr. 4	2880	0.75	–	–
6-46-20A	145	130x150	Arr. 4	2880	1.5	–	–
6-46-30A	210	180x180	Arr. 4	2880	3	803 555 360	850 1250 1400
6-46-40A	280	240x240	Arr. 4	1420	2.2	960 780 540	400 520 640
6-46-50A	350	300x300	Arr. 4	1440	5.5	1815 1530 1005	650 850 1050
6-46-60A	420	360x360	Arr. 4	1460	11	3280 2460 1800	950 1250 1500