

Mobile Mancoolers



- Australian made
- Australian Standard guards
- Class leading performance
- Heavy duty lifting hook fitted
- Large diameter wheel for easy handling
- Heavy pipe frame

- Aluminium/stainless steel
- Intrinsicly safe motors
- Hazardous locations (flameproof)
- Compressed air powered
- Custom build
- Corporate colours and labeled
- Sizes ranging from 400mm to 1,000mm diameter
- Motor Power - 0.18kW to 5.50kW
- Air Volume - 3,000L/s to 17,000L/s.
- Single or 3 Phase.

OPTIONS

Hydroblast Attachment

- Number of nozzles ranging from 2 to 4.



MODEL NUMBER	FAN DIA. (mm)	MOTOR SPEED (RPM)	MOTOR POWER (kW)	FREE AIR VOLUME (L/s)	VOLTAGE (V)
1-40241	400	1440	0.55	1500	240
1-40243	400	1440	0.55	1500	415
1-40481	400	2880	1.10	2150	240
1-40483	400	2880	1.10	2150	415
1-50241	500	1440	0.75	2450	240
1-50243	500	1440	0.75	2450	415
1-60241	600	1440	1.50	4400	240
1-60243	600	1440	1.50	4400	415
1-61241	600	1440	2.20	5800	240
1-61243	600	1440	3.00	6600	415
1-80163	800	960	1.50	7000	415
1-80241	800	1440	2.20	8000	240
1-80243	800	1440	3.00	9000	415
1-10123	1000	720	3.00	12000	415
1-80161	800	960	0.55	6800	240
1-10163	1000	960	5.50	17000	415

